

5430

Basic PMP Condensation Particle Counter

Precise and compact – for solid particle number (PN)

- n-Butanol based CPC
- Complies to the GPRE particle measurement program
- Prepared for external vacuum supply



Features

- Precise nanoparticle counting
 - n-Butanol based CPC
 - $D_{50} = 23.0 \text{ nm}$
 - Droplet size control
 - Continuous condensate drain with micro pump
 - Single count mode (up to 50 000 particles/cm³)
- Sample flow rate controlled by critical orifice
 - External vacuum required
- Saturator shutter
- Wide range power supply
 - 100 ... 240 VAC wide range power supply, 50 ... 60 Hz

Benefits

- Optimized for special applications
 - Measuring of solid particle number (PN)
 - Exhaust emission monitoring
 - Aerosol research
 - Testing of diesel particulate filter (DPF)
- Easy to use
 - Status control via LEDs
 - LCD display for real-time number concentration data
 - 5475 GRIMM nanoSoftware for Counters
- Cost saving
 - No moving parts
 - Low maintenance

Technical data

| | |
|--|---|
| Detection principle | Condensation particle counter |
| Working fluid | n-butanol (n-butyl alcohol) |
| Output | Particle number concentration/cm ³ |
| Particle concentration range | Single count mode: up to 50 000 particles/cm ³ |
| Coincidence correction | < 10% ... 23 000 particles/cm ³ |
| Concentration linearity | $R^2 \geq 0.98$ |
| Concentration accuracy | $\geq 90\%$ |
| Response time t₁₀ ... t₉₀ | < 2 s |
| Counting efficiency | at 23 nm $50 \pm 12\%$ at 41 nm $\geq 90\%$ |
| False background counts | < 0.001 particles/cm ³ |
| Readability | 0.1 particles/cm ³ |
| Sample flow rate | 0.6 l/min (requires external vacuum), independent of altitude above sea level |

| | |
|-------------------------------|---|
| Flow control | Critical orifice with stabilized temperature |
| Aerosol carrier gas | Air and inert gases |
| Interface | USB or RS-232 |
| Data recording | Directly on PC with GRIMM nanoSoftware, optionally on USB flash drive |
| Analog input | Port for optional analog sensor e.g. T, RH; $3 \times 0 \dots 10 \text{ V}$ |
| Power supply | 100 ... 240 VAC, 50 ... 60 Hz, max. 10.4 A |
| Power input | 40 W standard operation 30 W standby 80 W warm up |
| Dimensions (h x w x d) | <ul style="list-style-type: none"> • Housing: 23 x 26 x 24 cm (9 x 10.2 x 9.4 inch) • Fully assembled with n-butanol and condensate bottle: 35 x 26 x 29 cm (13.8 x 10.2 x 11.4 inch) |
| Weight | 8.9 kg (19.6 lbs) |
| Operating conditions | +10 ... +40 °C (50 ... 104 °F), RH < 95% non condensing, 500 ... 1 100 mbar |
| Transport and storage | 0 ... +50 °C (32 ... 122 °F), RH < 95% |