

Aerosol Neutralizers

Bipolar ion production with various ionization sources, ensuring a well-defined charging state of the aerosol

- Low maintenance and easy to use
- The right solution for any application
- Radioactive and non-radioactive ionization sources



FEATURES

- Am-241 α radioactive source
- Nominal activity 3.7 MBq
- Maximum energy 5.6 MeV
- Aerosol flow rate up to 5 l/min

TECHNICAL DATA

Ion generation method	Alpha (α) radiation, maximum energy 5.6 MeV
Aerosol flow rate	Up to 5 l/min
Maximum particle concentration	Up to 10^7 particle/cm ³
Aerosol medium	Air or N ₂
Source type	Am-241; sealed radioactive source; covered with gold layer
Nominal activity	3.7 MBq
Half-live	433 y

BENEFITS

- Optimized to be directly connected to GRIMM DMAs
- Compatible with GRIMM SMPS+C and SMPS+E systems
- Low maintenance
- Easy and safe to operate

Housing	Stainless steel
Dimensions (h x w x d)	4 x 5.5 x 5 cm (1.6 x 2.2 x 2 inch)
Weight	0.55 kg (1.2 lbs)



FEATURES

- Ni-63 β^- radioactive source
- Nominal activity 95 MBq
- Maximum energy 66 keV
- Aerosol flow rate up to 1 l/min

TECHNICAL DATA

Ion generation method	Beta (β^-) radiation, maximum energy 66 keV, no photons
Aerosol flow rate	Up to 1 l/min
Maximum particle concentration	Up to 10^7 particle/cm ³
Aerosol medium	Air or N ₂
Source type	Ni-63; unsealed radioactive source; cleaning not permitted
Nominal activity	95 MBq (+0/-10%)
Half-live	96 y

BENEFITS

- No handling license required* as activity below 100 MBq
- Compatible with GRIMM SMPS+C and SMPS+E systems
- Low maintenance
- Easy to operate and safe

Housing	Stainless steel with additional lead shielding
Dimensions (h x w x d)	18 x 6.9 x 6.9 cm (7.1 x 2.7 x 2.7 inch)
Weight	2.5 kg (5.5 lbs)



* One exemplar only allowed. Check local radiation protection directive.

FEATURES

- Non-radioactive source
- Dielectric barrier discharge plasma
- Aerosol flow rate 0.3 l/min
- Maximum particle concentration 10^6 particle/cm³

TECHNICAL DATA

Ion generation method	Dielectric barrier discharge plasma
Aerosol flow rate	0.3 l/min
Maximum particle concentration	Up to 10^6 particle/cm ³
Aerosol medium	Air (not useable with N ₂ , Ar or corrosive gases)
Ambient temperature	0 ... 40 °C (50 ... 104 °F)
Ambient humidity	20 ... 95% RH
Absolute pressure range	700 ... 1 100 mbar

BENEFITS

- Available as mobile (5520) and 19" version (5520-19")
- Compatible with GRIMM SMPS+C systems
- No transport/storing restrictions
- Easy and safe to operate

Power supply	100 ... 240 VAC, 50/60 Hz; 15 W
Dimensions (h x w x d)	18.0 x 6.9 x 6.9 cm (7.1 x 2.7 x 2.7 inch)
Weight	2.5 kg (5.5 lbs)



FEATURES

- Soft X-ray ion generation
- Non-radioactive source
- Maximum particle concentration 10^7 particle/cm³
- No particle, electromagnetic waves or ozone generation

TECHNICAL DATA

Ion generation method	Soft X-ray
Energy level	5524-X <11 keV 5525-X <4.99 keV
Aerosol flow rate	5524-X: 0.3 ... 5 L/min 5525-X: 0.3 ... 1.5 L/min
Maximum particle concentration	Up to 10^7 particle/cm ³
Aerosol medium	Air or N ₂
Equivalent X-ray dose	<0.13 µSv/h at 10 cm distance
Cooling	Natural cooling with ambient air

BENEFITS

- Available with <11 keV or <4.99 keV energy
- Compatible with GRIMM SMPS+C and SMPS+E systems
- No transport/storing restrictions
- Easy and safe to operate

Power supply	100 ... 240 VAC, 50/60 Hz; 7.2 W
Dimensions (h x w x d)	19.1 x 7.2 x 27.3 cm (7.5 x 2.8 x 10.8 inch)
Weight	1.11 kg (2.45 lbs)



GRIMM AEROSOL TECHNIK GMBH

OT Friedersdorf
Vordere Aue 4
06774 Muldestausee, Germany
Phone +49 3493 51407-0
info@grimm.durag.com

www.grimm-aerosol.com